


















January 2012

PIC	FEATURES	PROTOCOL	FREQUENCY	READING DISTANCE	DIMENSION	INTERFACE
 CY-EM100	60-10CM EM READER	EM-ID	125 KHz	60 - 100 cm	230 x 230 x 35 mm	* RS 232 / 485 * Weigand 26 bit
 CY-LR5	UHF PASSIVE 5M READER c/w brackets & PSU	ISO18000-6B ISO18000-6C	ISM 902 MHz 920 MHz	4 - 8 m	235 x 235 x 50 mm	* RS 232 / 485 * Weigand 26 bit
 CY-LR10	UHF PASSIVE 10M READER c/w brackets & PSU	ISO18000-6B ISO18000-6C	ISM 902 MHz 920 MHz	8-12 m	440 x 440 x 50 mm	* RS 232 / 485 * Weigand 26 bit
 CY-ALR	UHF ACTIVE 10M READER c/w brackets & PSU	ISO18000-6B ISO18000-6C	ISM 902 MHz 920 MHz	10m - 100m (environment & settings dependent)	440 x 440 x 50 mm	* RS 232 / 485 * Weigand 26 bit

Guard Tour

 GT-100RF	Tour Recorder	EM-ID	125 KHz			USB
	Guard ID tag	EM ID	125 KHz	2 cm		85 x 55 mm
	Checkpoint tag	EM ID	125 KHz	2 cm		
	Events Pouch - Customizable for many events	EM ID	125 KHz	2 cm		

Accessories

 CY-MT10	Metal tag - screw mounted or glued to number plate	ISO18000-6B ISO18000-6C	ISM 902 MHz 920 MHz	12 m	200 x 10 x 10.5 mm	Reader dependent
	UHF Long Range Passive Card	ISO18000-6B ISO18000-6C	ISM 902 MHz 920 MHz	10 m	85 x 55x0.84 mm	Reader dependent
	Dual-Frequency Passive Long range ISO printable card	UHF & EM	ISM 902 MHz 920 MHz	10 m	85 x 55x0.84 mm	Reader dependent
	Dual-Frequency Passive Long range ISO printable card	UHF & Mifare S50	ISM 902 MHz 920 MHz	10 m	85 x 55x0.84 mm	Reader dependent
	EM card Long Range clampshell	EM	EM ID	125 KHz	85 x 55 mm	85 x 55 mm
	EM card standard clampshell	EM	EM ID	125 KHz	85 x 55 mm	85 x 55 mm
	EM card ISO-type 0.84mm	Full color printing available	EM ID	125 KHz	70 - 100	85 x 55 mm
	Windshield Sticker	ISO18000-6B ISO18000-6C	ISM 902 MHz 920 MHz	10 m	65 x 40 mm	-
	Active Tag (Battery Operated)	ISO18000-6B ISO18000-6C	ISM 902 MHz 920 MHz	10 -100m	65 x 40 mm	-
	Windshield ISO Card Holder	Double-sided tape			9cm X 6cm	-